






For this drawing we reserve all rights. Without our permission it may neither be copied nor made accessible to third persons. All patent trademarks and other right in this drawing are expressly reserved by SPINEA Ltd.



**C** GROOVE FOR O-RING 94x1.5



#	i	Poznamka/ Note
B	55	Standard
C	69	Standard
E	123	Standard
F	103	Standard

Note:  
- MAIN RING MUST BE IN OPERATION FIXED  
18pcs SCREW M4 **B**

VER/INDEX	ZMENA	DATUM	PODPIS
-/2xc	Zmena K23-0083	13-Feb-23	Kotulakova
-/1xb	Zmena K22-0044	16-Jan-23	Ceslar
-/1xa	Zmena K20-0410	14-Jul-20	Ceslar
MATERIAL	-	T.O.	-
ROZM.-POLOT.	-	POC.KS	-
POM. ZAR.	-	TECHNOL.PREJ.	-
KONST.NAVRH	Ceslar	01-Apr-19	TECHNOL.ODSUH.
KONST.ODSUHL	Klucar	SCHVALIL	-
VYR. PREJ.	PLATI OD	-	-
TS 115-i-GHX-H35-0793		115GHx	-
NAZOV		TYP	-

NEKOTOVANE HRANY = 0.3x45°, ZAObLENIA R0.3 VSEOBECNE TOLERANCIE - STN EN 22768-mK			
HMOTNOST [kg]	2.883	MIERKA	1:1
MENO MODELU/ VERS.	115-000G_0793_P/ -1	POZICIA	-
MENO VYKRESU/VERS.	115-000G_0793_P/ -1		
LIST/LISTOV	1/1	ARTIKEL	309101-#00#
0-793 P00 #00-3		-/C	
CISLO VYKRESU		VER./INDEX	