







For this drawing we reserve all rights. Without our permission it may neither be copied nor made accessible to third persons.  
All patent trademarks and other right in this drawing and are expressly reserved by SPINEA Ltd.



CONFIDENTIAL  
HANDLING, STORAGE AND / OR OPERATION OF ANY SPINEA GEAR REDUCER OR ACTUATOR  
HAS TO COMPLY WITH THE CONDITIONS AND REQUIREMENTS SET FORTH IN  
SPINEA PRODUCT CATALOGUE AND THE RESPECTIVE USER MANUAL (WARRANTY CONDITION).

Note:  
- Main ring must be fixed in operation with  
18pcs of SCREW M5 St 12.9, TIGHTENING TORQUE 8Nm

#	i	Poznamka/ Note
B	53	Standard
F	133	Standard
H	109	Standard

Vers/Revs	Change	Date	Signature
-/1xg	Change: K22-0183	28-Feb-22	Jackovic
Material	-		
Semi-Product	-		Pieces
Attachment		Techn.Prepared	
Design Prepared	Klucar	10-Nov-20	Techn.Checked
Design Checked	Menyko		Confirmed
Manuf.Checked		Valid From	
TS 155-i-G-H55-0739		TS 155G	
Description		Type	

**SPINEA**  
EXCELLENCE IN MOTION

Undimensioned Edges = 0.3x45°			
Untoleranced Dimensions - STN ISO 2768-mK			
Weight [kg]	6.846	Scale	1:1.5
Model Name/ Vers.		155_000G_H55_0739_P/ -.1	
Drawing Name/Vers.		155_000G_H55_0739_P/	
Sheet/Sheets	1/1	ARTIKEL	-
0-739 P00 #00-3			-/g
Drawing-No			Vers/Revs