






For this drawing we reserve all rights. Without our permission it may neither be copied nor made accessible to third persons. All patent trademark and other right in this drawing and are expressly reserved by SPINEA Ltd.



Note:
- Main ring must be fixed in operation with 12pcs screw M3 St 12.9, tightening torque 1,9Nm
- Unsealed space, see assembly manual in catalogue TS G
- RECOMENDATION FOR SEALING MOTOR FLANGE:
Recommended tolerance for fitting diameter (Ø50 $\begin{smallmatrix} -0.03 \\ -0.06 \end{smallmatrix}$)

#	i	Poznamka/Note
A	35	Standard
B	47	Standard
D	63	Standard
E	89	Standard

CONFIDENTIAL
HANDLING, STORAGE AND / OR OPERATION OF ANY SPINEA GEAR REDUCER OR ACTUATOR
HAS TO COMPLY WITH THE CONDITIONS AND REQUIREMENTS SET FORTH IN
SPINEA PRODUCT CATALOGUE AND THE RESPECTIVE USER MANUAL (WARRANTY CONDITION).

Vers/Revs	Change	Date	Signature
Material	-		
Semi-Product	- -		Pieces -
Attachment		Techn.Prepared	
Design Prepared	Jackovic	20-Feb-23	Techn.Checked
Design Checked	Menyko		Confirmed
Manuf.Checked		Valid From	
TS 065-i-G-P6-0836*			TS 065G
Description		Type	

*	Hriadelova Zátka/ Shaft Plug	Zátka/ Plug	Note/ Poznamka
A	So zatkou/ With plug	So zatkou/ With plug	Standard
B	So zatkou/ With plug	Bez zátky/ Without plug	Na požiadanie/ On request
C	Bez zátky/ Without plug	So zatkou/ With plug	Na požiadanie/ On request
D	Bez zátky/ Without plug	Bez zátky/ Without plug	Na požiadanie/ On request

Undimensioned Edges = 0.3x45°, Rounding R0.3			
General Tolerances - STN EN 22768-mK			
Weight [kg]	0.707	Scale	1.5:1
Model Name/ Vers.		065_000G_P6-0836_P/ -.1	
Drawing Name/Vers.		065_000G_P6-0836_P/ -.1	
Sheet/Sheets	1/1	ARTIKEL	390652-xxxx
0-836 P*0 #00-3			-/-
Drawing-No		Vers/Revs	